

FIBERGLASS TRUSSES



Load Table 3 - SKP Series - (Allowable Deflection = L/360)

Designation	Span	Depth	Approx. Wt./ft.	Loads plf
15SKP1.5	15'-0"	18"	9.3	290
15SKP2	15'-0"	24"	9.4	370
15SKP2.5	15'-0"	30"	9.5	450
15SKP3	15'-0"	36"	9.6	540
15SKP3.5	15'-0"	42"	9.7	625
20SKP2	20'-0"	24"	8.8	210
20SKP2.5	20'-0"	30"	8.8	255
20SKP3	20'-0"	36"	8.9	310
20SKP3.5	20'-0"	42"	9	360
20SKP4	20'-0"	48"	9.1	410
25SKP2	25'-0"	24"	8.4	135
25SKP2.5	25'-0"	30"	8.5	165
25SKP3	25'-0"	36"	8.6	200
25SKP3.5	25'-0"	42"	8.7	230
25SKP4	25'-0"	48"	8.7	265
30SKP2	30'-0"	24"	8.2	90
30SKP2.5	30'-0"	30"	8.2	115
30SKP3	30'-0"	36"	8.3	135
30SKP3.5	30'-0"	42"	8.4	160
30SKP4	30'-0"	48"	8.4	185

FIBERGLASS TRUSSES



Load Table 4 - KP Series - (Allowable Deflection = L/360)

Designation	Span	Depth	Approx. Wt./ft.	Loads plf
15KP1.5	15'-0"	18"	11.5	450
15KP2	15'-0"	24"	11.6	500
15KP2.5	15'-0"	30"	11.7	575
15KP3	15'-0"	36"	11.8	670
15KP3.5	15'-0"	42"	11.9	765
20KP2	20'-0"	24"	10.9	285
20KP2.5	20'-0"	30"	11	335
20KP3	20'-0"	36"	11	380
20KP3.5	20'-0"	42"	11.1	435
20KP4	20'-0"	48"	11.2	490
25KP2	25'-0"	24"	10.5	180
25KP2.5	25'-0"	30"	10.6	220
25KP3	25'-0"	36"	10.6	245
25KP3.5	25'-0"	42"	10.7	280
25KP4	25'-0"	48"	10.8	315
30KP2	30'-0"	24"	10.2	125
30KP2.5	30'-0"	30"	10.3	145
30KP3	30'-0"	36"	10.4	170
30KP3.5	30'-0"	42"	10.4	195
30KP4	30'-0"	48"	10.5	220
35KP2.5	35'-0"	30"	10.1	105
35KP3	35'-0"	36"	10.2	125
35KP3.5	35'-0"	42"	10.2	140
35KP4	35'-0"	48"	10.3	160
35KP4.5	35'-0"	54"	10.3	180
40KP3	40'-0"	36"	9.9	95
40KP3.5	40'-0"	42"	10	105
40KP4	40'-0"	48"	10	120
40KP4.5	40'-0"	54"	10.1	135
40KP5	40'-0"	60"	10.1	150